





ORGANIC LIGHT-EMITTING DIODES

LIGHTING TOWARD A SUSTAINABLE ENVIRONMENT

Colleen Cleary (Undergraduate)

Leo Panish (HS Student)

Angelo Angeles (HS Teacher)

Dr. Reginald Eze (Mentor)

Dr. Yasser Hassebo (Mentor)

Objective

Changing the parameters of a simulated OLED and analyzing the effects of these changes on OLED emission patterns.

The results of this study provide a template for a potential OLED with enhanced colorbrilliance and brightness.

ORGANIC LIGHT EMITTING DIODE LIGHTING

- Introduction
 - What is an Organic Light-Emitting Diode?
 - OLEDs Compared to Other Light Sources
 - History and Applications of Organic Light-Emitting Diodes
 - How Does it Work?
- Method
- Results and Conclusion
- Why is it the Next Generation of Technology?

What is an OLED?

Organic

A compound that is carbon-based.

Light-Emitting Diode (LED)

An electronic device that emits light when an electrical current is applied to it.


What is an OLED?



http://www.osadirect.com/static/img/news/img20130708lgchem01.jpg


An area light source that contains layers of thin, flexible sheets of organic electroluminescent material.

What is an OLED?



http://assets.inhabitat.com/wp-content/blogs.dir/1/files/2011/09/UD-OLED2.jpg

Evolution of Light



Incandescent lamp
Compact fluorescent lamp
Linear fluorescent lamp
Light-Emitting Diode
Organic Light-Emitting Diode

Efficiency 17.5 lm/W 49-75 lm/W 67-110 lm/W up to 140 lm/W

120 lm/W

0.9 years 7.3 years 5.0 years 13.7 years 36.5 years

Lifetime

OLEDs vs. LEDs



https://upload.wikimedia.org/wikipedia/commons/f/f2/OLED EarlyProduct.JPG




http://www.noguge.com/thumbnail/l/led-lights-8.jpeg

- OLEDs are area sources
- Small enough to be used as pixels in a display
- Modern displays can be less than 1mm thick and weigh less than 4.5 lbs
- Can be made flexible

- LEDs are point sources
- Used to backlight LCD TVs
- Modern displays can be less than 1.5 inches thick and weigh less than 35 lbs
- Encased in epoxy (plastic capsule)

History of OLEDs

- 1950's: André Bernanose observed electroluminescence in organic materials.
- 1960: Martin Pope developed a technique to connect an electric current to organic crystals.



https://upload.wikimedia.org/wikipedia/ commons/a/aa/Martin_Pope.jpg



http://blog.virginiatoy.com/wp-content/uploads/ 2013/09/EDC-Glowsticks.jpg



http://i2.wp.com/www.stevehuffphoto.com/wp-content/uploads/2012/01/kodak-logo.jpg

 1987: Ching W. Tang and Steven Van Slyke at Eastman Kodak reported the first small-molecule OLED device.

Commercialization of OLEDs

 In 2003, Kodak began integrating OLED technology with their digital cameras.



http://cdn.itechnews.net/wp-content/ uploads/2009/01/sony-bravia-xel-1-ultraslim-oled-tv.jpg



http://http://img.tomshardware.com/de/ 2003/08/08/ fotokuenstler_bis_5_megapixel_16_digitalkam eras_im_fokus/kodak_d01.jpg




http://http://www.techbel3arabi.com/wp-content/uploads/2015/05/lg-wallpaper-tv.jpg

- In 2007, Sony announced the XEL-1, the first OLED TV.
- In 2015, LG unveiled the world's thinnest OLED TV.

How does an OLED work?

- Potential difference is applied to the two electrodes.
- Electrons travel from cathode to anode.
- Holes recombine with the electrons in the emissive layer.
- Energy is released as lightle and directed towards the substrate.




ORGANIC LIGHT EMITTING DIODE LIGHTING

- Introduction
 - What is an Organic Light-Emitting Diode?
 - OLEDs Compared to Other Light Sources
 - History and Applications of Organic Light-Emitting Diodes
 - How Does it Work?
- Method
- Results and Conclusion
- Why is it the Next Generation of Technology?


Refractive Index

- Property of materials
- Defined as n=c/v
- Used to determine values such as incident angle of the mîth layer




https://d2jmvrsizmvf4x.cloudfront.net/if5aenByR5yU8Nm5WsXF_refraction.jpg

Adding Microcavities and DBRs



"Microdisplays Based upon Organic Light-emitting Diodes." IBM Journal of Research and Development



Microcavity

Creates standing waves that amplify the light


DBR

Produces standing waves using phase change

Nine-Step Algorithm


- 1. User input values
- 2. Converting values for calculation
- 3. Outer loop for Incident angles (-90 degrees < q < 90 degrees)
- 4. Calculating Refracted angles and Layers thickness
- 5. Calculating the Optical admittance
- 6. Inner loop for Wavelength (Bragg wavelength +/- 180)
- 7. Calculating Phase factor and Characteristic Matrix
- 8. Computing the Transmittivity and Reflectivity values
- 9. Graphs

First Simulation




OLED with DBRs

Validity of Code




Liddell, Heather Mary., and H. G. Jerrard. "Periodic Multilayers and the Classical Stack." Computeraided Techniques for the Design of Multilayer Filters. Bristol: A. Hilger, 1981. 14-18. Print.

Validity of Code





Approach

Final Simulation



OLED with DBRs and a microcavity








Approach

- Goals:
 - Maximum transmission at Bragg wavelength
 - 2. Maximum reflection at surrounding wavelengths

- Focus on small bandwidth
- Parametric study








ORGANIC LIGHT EMITTING DIODE LIGHTING


- Introduction
 - What is an Organic Light-Emitting Diode?
 - OLEDs Compared to Other Light Sources
 - History and Applications of Organic Light-Emitting Diodes
 - How Does it Work?
 - Method
- Results and Conclusion
- Why is it the Next Generation of Technology?

Changing the number of DBR stacks above and below the cavity affects transmission.

Before



After




Unequal Stacks


Equal Stacks

Changing the substrate index affects maximum transmission.

Before



After




High Index


Low Index

Changing the cavity index affects reflection patterns.






After




Changing the length of the microcavity affects transmission at the Bragg wavelength.

Before



After



Bragg wavelength


Bragg Wavelength


Conclusion

For Maximum Transmission:

- Equal DBR stacks above and below cavity.
- 2. Substrate refractive index close to 1.0 (vacuum).
- 3. Cavity refractive index close to integer.
- 4. Cavity length of 1/2 or 1/4 the Bragg wavelength.

<u>Final</u>





ORGANIC LIGHT EMITTING DIODE LIGHTING

- Introduction
 - What is an Organic Light-Emitting Diode?
 - OLEDs Compared to Other Light Sources
 - History and Applications of Organic Light-Emitting Diodes
 - How Does it Work?
- Method
- Results and Conclusion
- Why is it the Next Generation of Technology?

Organic Light-Emitting Diodes ADVANTAGE DISADVANTAGE

S

- Energy efficient
- Environmentally friendly
- Does not emit heat or UV rays
- Closest light source to natural light
- Thinner and lighter than other light sources
- Cost decrease predicted to occur in the next 5 years
- Can be produced as large sheets
- Truer blacks and better contrast on displays

- Efficiency is still low compared to LED efficiency
- Blue OLED lifetime is much shorter than the red and green
- The cost to manufacture is currently expensive
- Sensitive to water and UV rays

Potential OLED Applications



http://www.superimaging.com/img/hud1.jpg



http://www.ledsmagazine.com/content/dam/leds/migrated/objects/news/6/7/10/GECIA_Clothes.jpg



http://www.demilked.com/magazine/wp-content/uploads/2014/10/windowless-passenger-plane-oled-touchscreen-walls-cpi-6.jpg

Sources

- 1. Heavens, O. S. Optical Properties of Thin Solid Films. London: Butterworths Scientific Publications, 1955. Print.
- 2. Geffroy, Bernard, Philippe Le Roy, and Christophe Prat. "Organic Light-emitting Diode (OLED) Technology: Materials, Devices and Display Technologies." *Polym. Int. Polymer International* 55.6 (2006): 572-82. Print.
- 3. Kalyani, N. Thejo, and S.j. Dhoble. "Organic Light Emitting Diodes: Energy Saving Lighting Technology— A Review." Renewable and Sustainable Energy Reviews 16 (2012): 2696-723. Print
- 4. "OLED Technology: Introduction and Basics." *OLED Technology: Introduction and Basics*. Web. 6 July 2015.
- 5. Howard, W. E., and O. F. Prache. "Microdisplays Based upon Organic Light-emitting Diodes." IBM Journal of Research and Development IBM J. Res. & Dev. (2001): 115-27. Print.
- 6. Burroughes, J.H. "Light-emitting Diodes Based on Conjugated Polymers." Nature 347 (1990): 352. Print
- 7. Antoniadis, Homer, Ph.D. "Overview of OLED Display Technology." Osram Optical Semiconductors. http://www.ewh.ieee.org/soc/cpmt/presentations/cpmt0401a.pdf
- 8. "DuPont shows new AMOLED materials and OLED displays" OLED-Info.com.
- 9. Howard, Webster E. "Better Displays with Organic Films." Sci Am Scientific American (2004): 76-81. Print.
- 10. "Kodak Unveils World's First Digital Camera with OLED Display" Eastman Kodak. 3/2/2003.
- 11. Michael J. Felton (2001) "Thinner lighter better brighter, Today's Chemist at Work."; 10 (11): 30-34
- 12. Williams, Martyn. "PC World Sony Readies OLED TV".4/12/2007.
- 13. Reisinger, Don. "LG Display Shows off Press-on 'wallpaper' TV under 1mm Thick CNET." CNET. 19 May 2015. Web. 6 July 2015.
- 14. Schubert, E. Fred. "Light Emitting Diodes and Solid-State Lighting." Light Emitting Diodes

Acknowledgements

National Aeronautics and Space Administration (NASA)

NASA Goddard Space Flight Center, Office of Education (GSFC)

NASA Goddard Institute for Space Studies (GISS)

NASA New York City Research Initiative (NYCRI)

LaGuardia Community College (LAGCC)

Samhita Roy, Student, WWP South
Dr. John R.E. Toland, Physics Professor, LAGCC







ORGANIC LIGHT-EMITTING DIODES

LIGHTING TOWARD A SUSTAINABLE ENVIRONMENT

Colleen Cleary (Undergraduate)

Leo Panish (HS Student)

Angelo Angeles (HS Teacher)

Dr. Reginald Eze (Mentor)

Dr. Yasser Hassebo (Mentor)







ORGANIC LIGHT-EMITTING DIODES

LIGHTING TOWARD A SUSTAINABLE ENVIRONMENT

Circuit Basics

Semiconductors

P-N Junction

Layers of an OLED

Excitons

Microcavity

DBR

OLED Materials

Equations

Applying the Layers

Algorithm Steps


Natural Light

Black Levels/Contrast

Home

Circuit Basics

- Potential difference (voltage) creates a push
- Current flows through circuit
- Resistance restricts flow
- Direct current and alternating current




http://www.rkm.com.au/ANIMATIONS/animation-graphics/circuit-diagram.jpg

Main Menu

Semiconductors

- Conductivity increases with temperature.
- Allows for greater control of current.
- Used in transistors, diodes, microprocessors.
- Usually Silicon and Germanium




http://lubricationtechnology.com/uploads/images/pageimages/semiconductor.png

Main Menu

P-N Junction

P Material

- Semiconductor doped with an impurity that has fewer valence electrons
- The missing electron leaves a positively-charged "hole"




N Material

- Semiconductor doped with an impurity that has extra valence electrons
- Extra electrons can move freely and conduct electricity


Main Menu

P-N Junction



Diffusion

Random movement of electrons to fill an entire space (no current)




Drift

Movement of electrons due to an electric potential (current)

P-N Junction

Forward Bias

- works with drift to decrease the depletion zone
- negative current pushes electrons across
- current created



circuitstoday.com/pn-junction-diode-characteristics


Reverse Bias

- works against drift and with diffusion
- increases the depletion zone
- negligible current

Current can only flow in one direction.

Basic OLED Structure

- Invented by Kodak in 1987
- Only two layers between cathode and anode.




Cathode and Anode

 Cathode: Electrode that receives electrons when connected to a power source

Typically a reflective metal

- Anode: Electrode that loses electrons (or "receives holes")
- Often transparent and made of indium tin oxide (ITO)



Emissive and Conductive Layers


- Thin organic material between cathode and anode
- Combined thickness: 100-150 nanometers
- Electrons are transported to the emissive layer (ETL)
- "Holes" travel through conductive layer (HTL)
- Electrons and holes recombine in the ETL
- Energy is released in the form of light

EMISSIVE LAYER

CONDUCTIVE LAYER


Substrate Layer

- A protective, transparent layer
- Light passes through the clear substrate




Recombination and Excitons

- Electrons and holes recombine.
- The recombination forms exciton and releases light.
- Exciton (electron-hole pair) is electrically neutral.



https://www.solarquotes.com.au/img/solar-pv-effect3.jpg


Microcavity




http://www.planetoitunes.com/sound-audio-theology/solmedia/standing_waves.gif

Main Menu

Distributed Bragg Reflector



http://www.batop.de/information/pictures/quarterwave_stack.jpg



http://www.webexhibits.org/causesofcolor/images/ content/11z.jpg

OLED Materials

Cathode

- Aluminium
- Silver
- Magnesium
- Indium
- Lithium-fluoride

Electron Transport Layer (ETL)

Tris-(8hydroxyquinoline) Aluminum

Emissive Layer

- Tris-(8hydroxyquinoline) Aluminum
- Coumarin
- Dichloromethane

Hole Transport Layer (HTL)

- Copper phthalocyanine
- Naptha phenyl benzidene

Anode

- Indium-tin oxide
- Zinc oxide

Mathematical Concepts

Characteristic Matrix

- Necessary in order to calculate reflection and transmission.
- There is a characteristic matrix for:

Upper DBR, M↓DBR↓1

Microcavity, *M↓Cavity*

Lower DBR, MJDBRJ2

The total characteristic matrix can be found using:

 $M \downarrow Total = M \downarrow DBR \downarrow 1 * M \downarrow Cavity * M \downarrow DBR \downarrow 2$

Mathematical Concepts

Reflection and Transmission Equations

- M\Total, a 2x2 matrix, contains real and imaginary parts.
- The top and bottom two elements of the matrix form two complex numbers, denoted as *B* and *C*, respectively.

It is possible to calculate the reflection and transmission, given by:

```
\frac{R=(y\downarrow 0*B-C/y\downarrow 0*B+C)(y\downarrow 0*B-C/y\downarrow 0*B+C)}{(y\downarrow 0*B+C)} T=4y\downarrow 0 Re(y\downarrow sub)/(y\downarrow 0*B+C)
```

Applying the Organic Layers

- Vacuum Thermal Evaporation (VTE):
 - Organic molecules are evaporated and condensed.
 - Kodak's original process.
 - Expensive and inefficient.
- Organic Vapor Phase Deposition (OVPD)
 - Carrier gas transports evaporated organic molecules
 - More efficient and less expensive.
- Inkjet Printing
 - Materials sprayed directly to substrate.
 - Most efficient and least expensive application technique.


Defining Parameters

Steps 1-2

User enters properties of the layers:

Number of layers
Angle of incidence
Index of refraction
Wavelength

 Convert from degrees to radians




http://www.schoolphysics.co.uk/age16-19/Optics/Refraction/text/Refraction /images/1.png

Calculating Material Properties Steps 3-5

- Test all possible initial incident angles (-90° to 90°)
- Find values:

 Incident angle of mîth layer, θ↓m

 Thickness of each layer,
 Optical admittance, y



Showing how the light behaves in the DBR structure


Changing Wavelengths Steps 6-7

- Test visible spectrum with each initial incidence angle
- Determines values for:

Phase change, *δ*↓*m*

Characteristic matrix, MIm

Total characteristic matrix, MJT



Showing the maximum and minimum reflection in the DBR layers.

Results

Steps 8-9

 Receive output when all possibilities have been checked. Includes:


Reflectance, R


Transmittance, T

Phase angle, Y, between R and T


 Produce graphs from results







Spectral Power Distribution



Black Levels and Contrast



Black displayed on an OLED TV (left) and LCD TV (right).